Rev. 1.0 - November 2014

Fiber Optic Wall Mount Cabinet



Description:

Wall-mounted fiber-optic cabinet for termination or distribution of optical fibers.

Features:

- Two models available.
- Two locking doors.
- Removable adapter panel for ST, FC, SC, LC adapters.
- Other adapters available per customer request.
- Complies with GR-449-CORE standards.
- Color - RAL 7035.
- ROHS Compliance.

Benefits:

- High quality pigtails, 1.5 m tight buffer.
- Splice trays (up to 24 fibers each).

Specifications and Dimensions:

Type	Width	Height	Depth	Connectors
A (medium)	380 mm	305 mm	85 mm	Up to 24 SC,ST,FC
B (big)	445 mm	485 mm	100 mm	Up to 48 SC,ST,FC
C (small)	300 mm	300 mm	80 mm	Up to 24 SC,ST,FC

Ordering Information:

RWM-_ _ _ __ _ _ _ _

Unit Type	
A	380x305x85 mm
B	445x485x100 mm
C	300x300x80 mm

Adapter Type A	
1	FC
2	SC Simplex
3	SC Duplex
4	LC Simplex
5	LC Duplex
6	LC 4 Channels
7	ST

Adapter B	
M	MM
S	SM
A	APC
O	OM3/4

Adapter Count	
00	None
06	6
12	12
18	18
24	24
36	36
48	48

RWM- [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ]

Splice Trays	
0	None
1	12
2	24
3	36
4	48
5	72
6	96

Pigtail Count	
00	None
12	12
24	24
36	36
48	48
72	72
96	96

Polish Type	
M	No fiber
N	Normal
P	PC
U	UPC
A	APC

Fiber Type	
N	None
5	50/125 (OM2)
6	62.5/125
7	G657A2 BI
9	9/125
O	OM3
G	OM4 BI

BI=Bend Insensitive

Example: **RWM-A1S12112U9**

[Unit Type= (A) 380x305x85mm, Adapter Type A=FC, Adapter B=SM, Adapter Count=12, Splice Trays=12, Pigtail Count=12, Polish Type=UPC, Fiber Type=9/125]